

Wired control units

Timers

TimeControl TC42

Timer*



- Preprogrammed date, time and switching time function
- Block switching function (Mon – Fri, Sat – Sun)
- Slide switch for easy changing between manual and automatic mode
- Astronomical function for the evening saves readjusting the switching time
- Holiday function and automatic summer/winter time adjustment
- Enables the programming of 2 freely selectable intermediate positions
- Blind mode: Exact adjustment of blind laths in touch mode

Item no. 4032 000 002 0

Colour	Alpine white
Rated voltage	230 – 240 V/AC / 50 – 60 Hz
Switching current	5 A / 230 V/AC at $\cos \varphi = 1$
Battery type	CR 2032
Degree of protection	IP20
Class of protection	II
Permissible ambient temperature	0 to +55 °C
Type of mounting	Flush-mounted 58 mm diameter, wall mounting

TimeControl TC52

Timer for light sensor*



Functions as the TC42, but also includes:

- Two different week, block and day switching programs can be set
- Astronomical function for morning and evening saves readjusting the switching time
- Light sensor SC43 can be connected

Item no. 4032 000 003 0

Colour	Alpine white
Rated voltage	230 – 240 V/AC / 50 – 60 Hz
Switching current	5 A / 230 V/AC at $\cos \varphi = 1$
Battery type	CR 2032
Degree of protection	IP20
Class of protection	II
Permissible ambient temperature	0 to +55 °C
Type of mounting	Flush-mounted 58 mm diameter, wall mounting

SC43 light sensor

- Cable can be shortened

Item no. 4032 000 004 0 (2 m cable)

Item no. 4032 000 005 0 (5 m cable)

* **Note:** Adapter frames can be found on page 66.

Dimensions

Functional principle – typical wiring diagrams

