

# Centronic radio control units

## Centronic EasyControl EC541A-II

### 1-channel hand-held transmitter




- Enables the programming of two intermediate positions
- Einzel-, Gruppen- oder Zentralsteuerung
- Integrated transmission pilot lights
- Rear labelling field
- Defined drive commands possible

#### Technical data

Centronic EasyControl EC541A-II	
Item number	4034 000 920 1
Rated voltage	3 V
Battery type	CR 2430
IP degree of protection	20
Class of protection	III
Permissible ambient temperature	-10 ... 55°C
Type of mounting	Hand-held device
Colour (control unit)	Black
Length of power line	0.0 m
Device cable length	0.0 m
Radio frequency (control unit)	915,3 MHz

#### Functional principle - sample wiring diagram



#### Master data

	Weight kg	GTIN / EAN Number	Customs tariff number
<b>4034 000 920 1</b>	0.131	4251852908501	85269200

\* Product weight without accessories  
5th September, 2023



# Centronic radio control units

## Centronic EasyControl EC541A-II

### 1-channel hand-held transmitter




- Enables the programming of two intermediate positions
- Einzel-, Gruppen- oder Zentralsteuerung
- Integrated transmission pilot lights
- Rear labelling field
- Defined drive commands possible

#### Technical data

Centronic EasyControl EC541A-II	
Item number	4034 000 920 0
Rated voltage	3 V
Battery type	CR 2430
IP degree of protection	20
Class of protection	III
Permissible ambient temperature	-10 ... 55°C
Type of mounting	Hand-held device
Colour (control unit)	White
Length of power line	0.0 m
Device cable length	0.0 m
Radio frequency (control unit)	915,3 MHz

#### Functional principle - sample wiring diagram



#### Master data

	Weight kg	GTIN / EAN Number	Customs tariff number
<b>4034 000 920 0</b>	0.129	4251852908495	85269200

\* Product weight without accessories  
5th September, 2023

