

Centronic radio control units

Radio transmitters

EasyControl EC541a-II

1-channel hand-held transmitter



- Enables the programming of 2 freely selectable intermediate positions
- Wall bracket with rear labelling panel
- Single or central control unit

Item no. 4034 000 920 0 (white)

Item no. 4034 000 920 1 (black)

Colour	White / black
Rated voltage	3 V/DC
Battery type	CR 2430
Degree of protection	IP20
Permissible ambient temperature	-10 to +55 °C
Radio frequency	915.3 MHz

EasyControl EC545a-II

5-channel hand-held transmitter



- 5 channels with LED display
- Enables the programming of 2 freely selectable intermediate positions
- Wall bracket with rear labelling panel
- Single, group or central control unit

Item no. 4034 000 921 0 (white)

Item no. 4034 000 921 1 (black)

Colour	White / black
Rated voltage	3 V/DC
Battery type	CR 2430
Degree of protection	IP20
Permissible ambient temperature	-10 to +55 °C
Radio frequency	915.3 MHz

EasyControl EC5410a-II

10-channel hand-held transmitter



- Easy-to-read 10-channel display with 3-coloured LEDs
- Enables the programming of 2 freely selectable intermediate positions
- Wall bracket with rear labelling panel
- Single, group or central control unit

Item no. 4034 000 922 0 (white)

Item no. 4034 000 922 1 (black)

Colour	White / black
Rated voltage	3 V/DC
Battery type	CR 2430
Degree of protection	IP20
Permissible ambient temperature	-10 to +55 °C
Radio frequency	915.3 MHz

Dimensions

Functional principle – typical wiring diagrams

