

# Centronic radio control units

## Centronic SunWindControl SWC245A-II

5-channel hand-held transmitter for setting wind threshold values



- Enables the programming of two intermediate positions per channel
- Einzel-, Gruppen- oder Zentralsteuerung
- Threshold values can be adjusted for each channel
- Setting the threshold values possible directly on the device
- Integrated transmission pilot lights
- Automatic mode can be activated/deactivated simultaneously for individual channels or all channels on the operating device directly
- Rear labelling field
- Defined drive commands possible

### Technical data

| Centronic SunWindControl SWC245A-II |                  |
|-------------------------------------|------------------|
| Item number                         | 4033 000 924 0   |
| Rated voltage                       | 3 V              |
| Battery type                        | CR 2430          |
| IP degree of protection             | 20               |
| Class of protection                 | III              |
| Permissible ambient temperature     | -10 ... 55°C     |
| Type of mounting                    | Hand-held device |
| Colour (control unit)               | White            |
| Length of power line                | 0.0 m            |
| Device cable length                 | 0.0 m            |
| Radio frequency (control unit)      | 915,3 MHz        |

### Dimensions



### Functional principle - sample wiring diagram

\* Product weight without accessories  
5th September, 2023



# Centronic radio control units

Centronic SunWindControl SWC245A-II

5-channel hand-held transmitter for setting wind threshold values



| Master data    | Weight<br>kg | GTIN / EAN<br>Number | Customs tariff<br>number |
|----------------|--------------|----------------------|--------------------------|
| 4033 000 924 0 | 0.148        | 4251852908440        | 85269200                 |

\* Product weight without accessories  
5th September, 2023



**BECKER**

# Centronic radio control units

## Centronic SunWindControl SWC245A-II

5-channel hand-held transmitter for setting wind threshold values



- Enables the programming of two intermediate positions per channel
- Einzel-, Gruppen- oder Zentralsteuerung
- Threshold values can be adjusted for each channel
- Setting the threshold values possible directly on the device
- Integrated transmission pilot lights
- Automatic mode can be activated/deactivated simultaneously for individual channels or all channels on the operating device directly
- Rear labelling field
- Defined drive commands possible

### Technical data

| Centronic SunWindControl SWC245A-II |                  |
|-------------------------------------|------------------|
| Item number                         | 4033 000 924 1   |
| Rated voltage                       | 3 V              |
| Battery type                        | CR 2430          |
| IP degree of protection             | 20               |
| Class of protection                 | III              |
| Permissible ambient temperature     | -10 ... 55°C     |
| Type of mounting                    | Hand-held device |
| Colour (control unit)               | Black            |
| Length of power line                | 0.0 m            |
| Device cable length                 | 0.0 m            |
| Radio frequency (control unit)      | 915,3 MHz        |

### Dimensions



### Functional principle - sample wiring diagram

\* Product weight without accessories  
5th September, 2023



# Centronic radio control units

Centronic SunWindControl SWC245A-II

5-channel hand-held transmitter for setting wind threshold values



| Master data    | Weight<br>kg | GTIN / EAN<br>Number | Customs tariff<br>number |
|----------------|--------------|----------------------|--------------------------|
| 4033 000 924 1 | 0.132        | 4251852908457        | 85269200                 |

\* Product weight without accessories  
5th September, 2023



**BECKER**