

Universal sun protection drives with integrated Centronic PLUS radio receiver

for barrels with 38 mm or larger diameter

P4-30-C12a PLUS...P5-20-C12a PLUS



Suitable for:

- Drop-arm awning
- Open/semi-open articulated-arm awning

- Articulated-arm cassette awning
- Markisolette/window awning
- Conservatory awning
- Pergola

- Horizontal screen
- Guided
- Volants



Blockage detection in both directions with automatic reversal and multiple testing



Enables programming of 2 freely selectable intermediate positions



Memory function: Integrated timer can be activated via MemoControl transmitter



Fabric untensioning can be switched on/off in the upper limit position



Optional activation: Fabric tensioning function



Higher closing force for cassette awnings



The mesh technology allows individual drives to connect together automatically to form a very efficient network



Compatible with sun/wind/rain sensors for maximum convenience



Wireless software update via DECT central controls, e.g. FRITZ!Box



Made in Germany - for maximum reliability and durability



Supports parallel connection



C-Plug pluggable connecting cable



Integrated CentronicPlus radio transceiver: the drive reports back its position, any blockage and other status information



Centronic radio receiver integrated: compatible with Centronic range of control units



Individual, group and central control possible (also by radio)



Local operation with a standard single button



Lower limit position adjustment: point (automatic detection or freely programmable), Upper limit position adjustment: point or stop



Auto-install function



Intelligent installation management permits limit position corrections



Switchable stop behaviour



Limit positions status indicator (LSI) signals missing limit positions



Automatic shading solution length adjustment



Convenient threshold adjustment via the hand-held transmitter or central control units



Switch on the motor head to change the direction of rotation and to activate and deactivate programming mode

* C-plug connecting cables are available in various versions and lengths and must be ordered separately.

** Drive adapter width from 40 x 1/42 x 2 (4930 300 086 0), when selecting a different drive adapter, the dimensions L2, L3 and L5 will change

*** Product weight without accessories



Universal sun protection drives with integrated Centronic PLUS radio receiver

for barrels with 38 mm or larger diameter

P4-30-C12a PLUS...P5-20-C12a PLUS



Technical data

	Item number	Torque Nm	Speed (idling) U/min	Limit switch range Umdr.	Rated current A	Power consump. W	Connecting cable (m)
P4-30-C12a PLUS	2009 130 175 0	4	30	64	0.45	110	*
P5-20-C12a PLUS	2009 130 174 0	5	20	64	0.45	110	*

Rated voltage: 240 V / 50 Hz / ~ AC

IP degree of protection: 44

Operating mode: S2 4 min

Dimensions (in mm)

	L ₁	L ₂ **	L ₃ **	L ₄	L ₅ **	diam. c
P4-30-C12a PLUS	453.00	470.00	483.00	13.00	17.00	35
P5-20-C12a PLUS	453.00	470.00	483.00	13.00	17.00	35

Master data

	Item number	Weight kg	GTIN / EAN Number	Customs tariff number
P4-30-C12a PLUS	2009 130 175 0	1.147		85014020
P5-20-C12a PLUS	2009 130 174 0	1.118		85014020

* C-plug connecting cables are available in various versions and lengths and must be ordered separately.

** Drive adapter width from 40 x 1/42 x 2 (4930 300 086 0), when selecting a different drive adapter, the dimensions L2, L3 and L5 will change

*** Product weight without accessories

23rd October, 2024



BECKER